

COMPACT WITH A HIGH FILTER VOLUME

FiltoSmart 60 – External Aquarium Filter

Easy to open

Easy slide opening mechanism

Self-priming

Engineered for fast and easy startup and continued operation

Space-saving

Compact size and stable base allow the filter to be placed discreetly next to or behind the aquarium



2-stage filtration: biological and mechanical filtration

Energy-efficient

Quiet operation

Complete set for a quick start

Includes filter media, intake tube with inlet strainer, water distributor nozzle, spray bar, inlet and outlet adapters, tubing, and fittings



Accessories (not included)

Easily attach the FiltoSmart 60 to the side of your aquarium with the FiltoSmart Bracket (Item no. 48627).

FiltoSmart		60
Dimensions (L x W x H)	in.	5.9 x 3.5 x 6.5
Dimensions (L x W x H)	mm	150 x 90 x 164
Rated voltage		120 V / 60 Hz
Power consumption	W	4
Power cable length	ft.	6
Max. flow rate	gph (l/h)	80 (300)
Max. head height	ft. (m)	2.3 (0.7)
Inlet/outlet connection unit, fits tubing		10 mm, 3/8" ID
Tubing	inner Ø x L	3/8 in. ID x 3.3 ft. (8 mm x 1 m)
Filter volume	gal (l)	0.13 (0.5)
Pre-filter volume	gal (l)	0.07 (0.28)
Suitable for aquariums up to max.	gal (l)	20 (60)
Suitable for		fresh water and marine water
Warrant	years	3
Item no.		55158