

PRECISION TEMPERATURE CONTROL

HeatUp 25 to 400 – Adjustable Heater



Function control

The heating function is displayed via the activated control light

Accurate temperature adjustments

Temperature scale can be adjusted between 66°F - 90°F. A secondary control knob allows for precise readjustment of the temperature within +/- 2°F

Filter integration capabilities

Integrate HeatUp 50-300 into OASE internal & external filters to combine filtration and heating into one location.

Uniform temperature levels

Temperature levels are monitored and controlled by bi-metal technology for automated heating. Includes a thermal shutoff switch for added protection.



Easy installation

Includes holder with suction cups and integrated post calibration tool

Durable

High quality, double insulated quartz glass. Created to withstand greater temperature fluctuations than glass.

Fresh and marine water compatible



		NEW!						
HeatUp		25	50	100	150	200	300	400
Dimensions (Dia x H)	in.	0.9 x 8		0.9 x 9.6	0.9 x 12		0.9 x 14.6	0.9 x 17.3
Dimensions (Dia x H)	mm	23 x 205		23 x 243	23 x 315		23 x 370	23 x 243
Rated voltage		115V / 50-60 Hz						
Power consumption	W	25 W	50 W	100 W	150 W	200 W	300 W	400 W
Power cable length	ft.	5						
Net weight	lbs.	0.4		0.5	0.55		0.6	0.7
Suitable for aquariums up to max.	gal (l)	10 (25)	15 (50)	30 (100)	40 (150)	55 (200)	80 (300)	106 (400)
Suitable for		fresh water and marine water						
Works with		-	BioPlus 50	BioPlus 100, FiltoSmart 100	BioMaster 250	BioPlus 200, FiltoSmart 200, BioMaster 350	FiltoSmart 300, BioMaster 600	BioMaster 850
Warranty	years	3						
Item no.		33798	33799	33802	33803	33804	33805	77117